

ABETONE CLUB

RADICI
CARPET



COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
MOQUETTE WILTON SUPERFICIE VELLUTO-RICCIO	WILTON CARPET CUT/LOOP PILE	MOQUETTE WILTON À VELOURS COUPÉ-BOUCLÉ	WILTON TEPPICH SCHNITT-SCHLINGENPOL
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% LANA	100% WOOL	100% LAINE	100% WOLLE
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA/SINTETICO	JUTE/SYNTHETIC	JUTE/SYNTHÉTIQUE	JUTE/SYNTHETIK
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 96000	± 96000	± 96000	± 96000
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 6 mm	± 6 mm	± 6 mm	± 6 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 8 mm	± 8 mm	± 8 mm	± 8 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 1211 g/m ²	± 1211 g/m ²	± 1211 g/m ²	± 1211 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2207 g/m ²	± 2207 g/m ²	± 2207 g/m ²	± 2207 g/m ²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA WILTON 100% LANA	FAMIGLIA WILTON 100% LANA	FAMIGLIA WILTON 100% LANA	FAMIGLIA WILTON 100% LANA

Note-Marine Equipment Fire certification: range certified



COMFORT: ★★★★★

BUSINESS WEARABILITY: ★★☆☆

DOMESTIC WEARABILITY: ★★★☆☆

Colour fastness to light	≥ 5 (4 PASTEL SHADE)	Thermal resistance m ² K/W	≤ 0,17
Insulation impact noise ΔLw	32 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,23		

Radici Pietro Industries & Brands Spa - 24026 Cazzano Sant'Andrea (BG) Italia - www.radiciacarpets.it - info@radiciacarpets.it

Radici Pietro I&B. reserves the right to modify the characteristics of the product while keeping the same technical properties

TSO1/2023