


# OASI

**(OUTDOOR FLAT WOVEN)**

**EN14041 : 2004**


Specifications and tolerances in according EN 1307

COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TESSUTO RICCIO	WOVEN-LOOP PILE	TISSEE-BOUCLE	GEWEBT SCHLINGE
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIPROPILENE	100% POLYPROPYLENE	100% POLYPROPYLENE	100% POLYPROPYLEN
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
SBR COATING	SBR COATING	SBR COATING	SBR COATING
PUNTI AL M <sup>2</sup>	STITCHES PER M <sup>2</sup>	TOUFFES AU M <sup>2</sup>	KNOTEN M <sup>2</sup>
± 224000	± 224000	± 224000	± 224000
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 6.0 mm	± 6.0 mm	± 6.0 mm	± 6.0 mm
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 1600 g/m <sup>2</sup>	± 1600 g/m <sup>2</sup>	± 1600 g/m <sup>2</sup>	± 1600 g/m <sup>2</sup>
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm


**COMFORT:** ★☆☆☆☆

**DOMESTIC WEARABILITY:** ★★★

Colour fastness to light	≥ 5
Insulation impact noise ΔLw	22 dB
Thermal resistance m <sup>2</sup> K/W	≤ 0,10