


WOOL DECOR 1400

RADICI
CARPET



Specifications and tolerances in according EN 1307



STAINADVERSE

COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING VELLUTO STAMPATO 1/8"	TUFTED CUT PILE PRINT 1/8"	TUFTED VELOURS IMPRIMÉ 1/8"	GETUFTED DRUCKVELOURS 1/8"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
80% LANA 20% POLIAMMIDE	80% WOOL 20% POLYAMID	80% LAINE 20% POLYAMIDE	80% WOLLE 20% POLYAMID
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M²	STITCHES PER M²	TOUFFES AU M²	KNOTEN M²
± 173250	± 173250	± 173250	± 173250
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 7.3 mm	± 7.3 mm	± 7.3 mm	± 7.3 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 10 mm	± 10 mm	± 10 mm	± 10 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 1400 g/m²	± 1400 g/m²	± 1400 g/m²	± 1400 g/m²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2500 g/m²	± 2500 g/m²	± 2500 g/m²	± 2500 g/m²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 6	FAMIGLIA TUFTING 6	FAMIGLIA TUFTING 6	FAMIGLIA TUFTING 6



COMFORT: ★★★★★

BUSINESS WEARABILITY: ★★

DOMESTIC WEARABILITY: ★★

Colour fastness to light	≥ 5 (4 PASTEL SHADE)	Thermal resistance m2 K/W	≤ 0,17
Insulation impact noise ΔLw	33 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,26		