

# NAPOLI-NAPOLI LINEA

**RADICI**  
CARPET



COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO 1/10"	TUFTED LOOP PILE 1/10"	TUFTED BOUCLÉ 1/10"	GETUFTED SCHLINGE 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE SD	100% POLYAMIDE SD	100% POLYAMIDE SD	100% POLYAMID SD
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
POLYFLEX	POLYFLEX	POLYFLEX	POLYFLEX
PUNTI AL M <sup>2</sup>	STITCHES PER M <sup>2</sup>	TOUFFES AU M <sup>2</sup>	KNOTEN M <sup>2</sup>
± 187000	± 187000	± 187000	± 187000
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 3.5 mm	± 3.5 mm	± 3.5 mm	± 3.5 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 5.4 mm	± 5.4 mm	± 5.4 mm	± 5.4 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 550 g/m <sup>2</sup>	± 550 g/m <sup>2</sup>	± 550 g/m <sup>2</sup>	± 550 g/m <sup>2</sup>
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 4100 g/m <sup>2</sup>	± 4100 g/m <sup>2</sup>	± 4100 g/m <sup>2</sup>	± 4100 g/m <sup>2</sup>
DIMENSIONI QUADROTTA	TILE SIZE	TAILLES DES DALLE	GESAMTGEWICHT
50x50 cm	50x50 cm	50x50 cm	50x50 cm
FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26	FAMIGLIA TUFTING 26



**BUSINESS WEARABILITY: ★ ★ ★**

Colour fastness to light	> 5	Thermal resistance m <sup>2</sup> K/W	≤ 0,17
Insulation impact noise ΔLw	24 dB	Body voltage walking test kV	≤ 2