


ROOM DECOR

RADICI
CARPET



Specifications and tolerances in according EN 1307



STAINADVERSE



COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING VELLUTO STAMPATO 1/10"	TUFTED CUT PILE PRINTED 1/10"	TUFTED VELOURS IMPRIMÉ 1/10"	GETUFTED DRUCKVELOURS 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE	100% POLYAMID	100% POLYAMIDE	100% POLYAMID
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 146150	± 146150	± 146150	± 146150
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 7.5 mm	± 7.5 mm	± 7.5 mm	± 7.5 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 10.5 mm	± 10.5 mm	± 10.5 mm	± 10.5 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 1050 g/m ²	± 1050 g/m ²	± 1050 g/m ²	± 1050 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2040 g/m ²	± 2040 g/m ²	± 2040 g/m ²	± 2040 g/m ²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1



COMFORT: ★★★★★☆

BUSINESS WEARABILITY: ★★★☆

DOMESTIC WEARABILITY: ★★★

This product is recyclable. For more information, please contact us at info@radicicarpet.it

Colour fastness to light	≥ 5	Thermal resistance m2 K/W	≤ 0,17
Insulation impact noise ΔLw	29 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,20		